

MEESKONNALIIGE, KELLETA SA HAKKAMA EI SAA.

Lubage tutvustada meie meeskonna kõige uuemat liiget - see on kompaktne A3 värviline P-C2480i MFP süsteem. Mida see seade oskab? Eelkõige on ta suure töövõimega, lihtsasti käsitletav, kompaktne ja diskreetne. Samas teeb tööd efektiivselt ja on lõputult kohanemisvõimeline. Seade on hästi kokku pandud ja valmis tegema kõike, olgu selleks näiteks tundliku informatsiooni säilitamine, P-C2480i MFP annab salajast teavet kätte vaid peale kasutaja tuvastamist. See masin on tõeline võlur, kui asi puudutab printimist, skaneerimist, kopeerimist või isegi faksimist* - ja ta on alati kohal, et Sinu käsklusi täita.



DIGITAALNE MULTIFUNKTSIONAALNE
 VÄRVILINE SÜSTEEM

P-C2480i MFP

kopeerimine / printimine /
skaneerimine / faks

A3

KÕRGHETKED:



Erakordselt kiire: P-C2480i MFP prindib ja skaneerib 24 A4 lehte minutis värviliselt ja mustvalgelt. Esimene leht on trükitud ja valmis peale ca 10 sekundit. Seade on ka ülimalt efektiivne - võimeline skaneerima kuni 50 lehte minutis. Kui eelistad siiski kiirusele kvaliteeti, on Sul võimalik printida ekstra terava resolutsiooniga 1200 x 1200 dpi.



Väga mobiilne: Tasuta Mobile Print äpp lubab Sul lihtsasti seadmele ligi pääseda otse oma nutitelefoni või tahvelarvutist ning printida ja skaneerida nõ. käigu pealt.

Kui valid Wi-Fi kaardi saad ühendada kuni kolm mobiilset seadet ... tänu Wi-Fi Direct*. Sul on võimalik kasutada ka NFC (near-field communication), et luua õhendus MFP ja oma mobiilse seadme vahel. See annab Sulle võimaluse tunda sellist sõltumatus tunnet, mida Sa poleks kunagi suutnud ette kujutada.



Ülimalt intelligentne: Seadme P-C2480i MFP intelligentsed funktsioonid aitavad Sind igal sammul. Üheks näiteks on "jäta vahele tühjad lehed"

funktsioon, mis jätab automaatselt välja tühjad lehed kopeerimisel ja skaneerimisel, säästes Sind seeläbi käsitsi sorteerimise vajadusest. Teine näide on ID-kaardi kopeerimise funktsioon, mis võimaldab printida kahepoolselt väikesformaadilisi dokumente nagu näiteks ID-kaart ja juhiloa. Võimalik on installida ka selliseid rakendusi nagu Scan2OCR (for creating text searchable documents), follow-me printing või arhiveerimislahendusi, kõike seda tänu integreeritud HyPAS liidesele.



Eriti paindlik: Oma 3 x 500-lehelise universaalse paberkasseti* ja 100-lehelise multi-käsisööduga, suudab P-C2480i MFP töödelda erineva formaadiga (A6 kuni A3) ja kaaluga (60 kuni 256 g/m²) paberit. See tagab selle, et oled alati hästi ette valmistunud ükskõik milliseks ülesandeks. Lisaks sellele garanteerib sisseehitatud töödeeraldaja, et kõik dokumendid on käepäraselt ja selgelt ära sorteeritud väljundsalves kohe kui väljatrükk on teostatud.

P-C2480i MFP

TEHNILISED ANDMED

IF IT WORX, IT'S



Üldine informatsioon

Tüüp	Lauapealne seade
Funktsioon	Kopeerimine, printimine, skaneerimine, valikuline: faks
Print. tehnoloogia	Laser värviline ja mustvalge
Originaalformaad	max A3 from platen glass
Originaalsöötja	50 sheet A4 (standard), min 140 x 182 mm, max 297 x 432 mm, 45-160 g/m ²
Kop. kiirus	(simplex), 50-120 g/m ² (duplex) max 24 A4 pages/min and max 12 A3 pages/min in colour and b/w
Esimene leht (copy/print)	9.8 seconds in colour and 7.6 seconds in b/w (copy)*, 10.2 seconds in colour and 7.5 seconds in b/w (print)*
Warm-up time	
Copy resolution	30 seconds
Greyscales	600 x 600 dpi
Paper feed	256
Paper weights	1 x 500 sheet universal cassette [A5R-A3], 100 sheet multi-bypass [A6R-A3]
Paper output	Universal cassette 60-256 g/m ² , multi-bypass 60-256 g/m ² , duplex 60-220 g/m ²
Job separator	250 sheet A4
System memory	30 sheet A4 (standard)
Continuous copying	1,998 copies, max. 3,072 GB RAM, 32/128 GB SSD**
Zoom	25%-400% in steps of 1%
Functions	Colour touch screen (4.3 inch), duplex, direct printing from/scanning to USB stick, job reservation, N-up, Favorites, 100 management codes, etc.

Dimensions/Weight

Dimensions	753 x 590 x 590 mm (H x W x D)
Weight	approx. 76 kg

Environment

Mains voltage	220/240 V, 50 Hz
Power consumption	approx. 850 W max., approx. 550 W in operation, approx. 70 W in stand-by mode, approx. 0.5 W in sleep mode, TEC value: 1.0 KWh/week
Noise level	approx. 48.3 dB(A)/47.3 dB(A) in operation (colour / b/w), approx. 30.8 dB(A) in stand-by mode (ISO 7779/9296)
Safety	GS/TÜV, CE

Print System

Type	Integrated within the system
Print format	A6R-A3
Print resolution	600 x 600 dpi, max 1,200 x 1,200 dpi (reduced speed)
Processor	ARM Cortex-A9 Dual Core/1.2 GHz
Interfaces	USB 2.0, 10/100/1000BaseTX, USB host (2), NFC, Wi-Fi**
Network protocols	TCP/IP, Net BEUI
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016, Novell NetWare**, Linux, Mac ex OS 10.5
Emulations	PCL6 (PCL 5c, XL), KPDL 3 (PostScript 3 compatible), PRESCRIBE IIc, PDF 1.7, XPS
Functions	Colour Optimiser, USB direct printing, PDF/XPS direct printing, printing of e-mails, private printing, barcode printing, Mobile Print (Android/iOS), Apple AirPrint, Google Cloud Print. Wi-Fi**

Scan system

Scan type	CIS colour and b/w
Scan format	max A3
Scan speed	b/w: max 50/16 A4 originals/min (simplex/duplex) with 300 dpi, colour: max 50/16 A4 originals/min (simplex/duplex) with 300 dpi
Scan resolution	200 dpi, 300 dpi, 400 dpi, 600 dpi
Scan mode	Photo, text, photo/text, optimised for OCR
File types	TIFF, PDF, XPS, OpenXPS, high compression PDF, JPEG
Interfaces	10/100/1000BaseTX, USB 2.0
Network protocol	TCP/IP
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016
Functions	Scan to SMB, scan to e-mail, scan to FTP, scan to USB, TWAIN scan, WIA scan, SMTP authentication, LDAP

Optional fax system (13)

Compatibility	Super G3
Original format	max A3
Modem speed	33.6 kbps
Transmission speed	3 seconds or less using JBIG
Compression method	JBIG, MMR, MR, MH
Fax resolution	Standard (200 x 100 dpi), fine (200 x 200 dpi), super fine (200 x 400 dpi), ultra fine (400 x 400 dpi)
Fax memory	16 MB (max 12 MB image memory)
Abbreviated dial	200 numbers
One touch dial	100 numbers
Group dial	50 numbers
Operating systems	Windows 7/8/8.1/10, Server 2008 R2/2012 R2/2016
Functions	Network fax driver, automatic redialling, delayed transmission

Options

Paper feed	PF-470 (max 1 x 500 sheet universal cassette (A5R-A3)), PF-471 (max 2 x 500 sheet universal cassettes (A5R-A3))
Other options	Data Security Kit (E), Card Authentication Kit (B), UG-33 ThinPrint® kit, IB-50 Gigabit Ethernet card, IB-36 or IB-51 WLAN card, HD-6 SSD (32 GB), HD-7 SSD (128 GB), cabinet no. 62

*Depending on operating status.

**optional

To enable HYPAS functionality additional memory is required.

Specifications subject to change without notice.

Image shows machine with optional accessories.

The P-C2480i MFP is manufactured in accordance with the requirements of the Energy Star Program.

UTAX has been a trade mark for professional office technology since 1961. As the partner of a German wide dealer network and international distribution, we are specialised in the distribution and integration of printing, copying and multifunctional systems in corporate IT and public sector, amongst others. With the MDS solution UTAX smart for example, output systems can be controlled regardless of the manufacturer and the infrastructure can be optimised in line with demands. UTAX recommends the use of original UTAX accessories for trouble-free operation of your system. For recommended print media refer to the user manual. UTAX and the UTAX logo are registered trade marks of TA Triumph-Adler GmbH. All other brand names referred to are registered trade marks of the respective manufacturers.

